

RS Series

Electric Scissor Lifts

JLG[®]
reachingout



RS Series
ELECTRIC SCISSOR LIFTS



3248RS

- 32 ft platform height
- 705 lb capacity



1932RS

- 19 ft platform height
- 500 lb capacity

Longer Runtime

The direct electric drive delivers industry-leading duty cycles similar to the ES Series.



Low Cost of Ownership

Passive pothole protection eliminates all moving parts in the pothole protection system, reducing the need for repair or replacement.



Easy Access

Battery storage area is easily accessible and has no drawer to pull out.



25% Gradeability

Both models have the ability to load without assistance and traverse grades of up to 25%.

On-Board MDI Display

The Multifunction Digital Indicator simplifies battery evaluation and fault diagnosis.



Always Ready to Work.

From commercial construction to hospitals, schools and facilities maintenance applications, the RS Series can be used virtually anywhere there's work to be done. The ruggedness of the RS Series make these machines extremely reliable. It's the value you need without sacrificing performance and quality.



Extremely Mobile

Innovative operator controls, similar to the ES Series, and tight turning radius provide ease of use and job site mobility.



RS Series
ELECTRIC SCISSOR LIFTS

Specifications

1932RS

3248RS

Dimensional Data

Platform Height – Elevated	19 ft (5.8 m)	32 ft (9.75 m)
Platform Height – Lowered	3 ft 3.2 in. (.996 m)	4 ft 7 in. (1.40 m)
Platform Railing Height	3 ft 4.2 in. (1.016 m)	3 ft 4.5 in. (1.03 m)
Overall Height	6 ft 7.4 in. (2.02 m)	7 ft 11 in. (2.41 m)
With Rails Lowered	N/A	6 ft 6 in. (1.98 m)
Platform Dimensions	6 ft x 2 ft 3 in. (1.82 m x .68 m)	42.5 x 84.7 in. (1.08 m x 2.15 m)
Platform Extension	28 in. (.7 m)	3 ft (.9 m)
Overall Machine Length	6 ft 9.4 in. (2.07 m)	7 ft 6.6 in. (2.30 m)
Overall Machine Width	32 in. (.812 m)	48 in. (1.22 m)
Wheelbase	55 in. (1.39 m)	73 in. (1.85 m)
Ground Clearance (midframe)	3.1 in. (7.87 cm)	4.1 in. (10.4 cm)
Platform Capacity	500 lb (227 kg)	705 lb (320 kg)
Capacity on Deck Extension	250 lb (113 kg)	250 lb (113 kg)
Lift/Lower Time	25/26 sec	60/60 sec
Maximum Drive Height	19 ft (5.8 m)	32 ft (9.75 m)
Weight	3,000 lb (1,360 kg)	5,070 lb (2300 kg)
Ground Bearing Pressure	143 psi (10.05 kg/cm ²)	90 psi (6.33 kg/cm ²)

Chassis

Drive Speed, Lowered	2.5 mph (4 km/h)	2.5 mph (4 km/h)
Drive Speed, Elevated	.3 mph (.48 km/h)	.3 mph (.48 km/h)
Gradeability	25%	25%
Turning Radius (Inside)	2 ft (.6 m)	4 ft (1.22 m)
Turning Radius (Outside)	7 ft 3 in. (2.2 m)	10 ft 5 in. (3.18 m)
Tire Size (Solid, Non-Marking)	12.5 x 4 in. (3.18 x 10 cm)	16 x 5 in. (41 x 13 cm)

Power Source

Batteries	4 x 6V, 220 AH	4 x 6V, 220 AH
Charger	25 amp	25 amp
Pump	3.2 cc/rev @ 2,300 psi (3.2 cc/rev @178 kg/cm ²)	3.2 cc/rev @ 2,500 psi (3.2 cc/rev @178 kg/cm ²)
Hydraulic Reservoir	1.32 gal (5 L)	2.38 gal (9 L)
Brakes (On Drive Wheels)	Electric, Friction	Electric, Friction
Guard Rail Type	Fixed	Fold-Down
Drive	24V DC	24V DC

Standard Features

110V-AC Receptacle in Platform	X	X
Fold-Down Guard Rails	N/A	X
Automatic Traction Control (ATC)	X	X
Flashing Amber Beacon	Optional	Optional
25 Amp Automatic SCR Charger	X	X
All Motion Alarm	X	X
Horn	X	X
Hourmeter	X	X
Pipe Racks	N/A	Optional
Lanyard Attach Points	X	X
Lubrication-Free Scissor Arm Bushings	X	X
Fork Lift Pockets	X	X
Tilt Alarm and Light	X	X
Battery Condition Indicator	X	X



Ground Support®

When it comes to Ground Support, it's all about you. Your productivity. Your profitability. Your uptime. From the purchase of your first piece of equipment straight through to the training, parts and maintenance that follows. Whatever your needs, we're here to support you.

JLG Industries, Inc.
1 JLG Drive
McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

An Oshkosh Corporation Company

Part No.: 3131504
R031201
Printed in USA

